

EOS 5DIV Custom Shooting Modes, Use Cases and Camera Settings ([download PDF](#))

S e t u p	Shooting Mode	Normal Mode	C1 Custom Mode	C2 Custom Mode	C3 Custom Mode	
	Use Cases	General Purpose, Portrait	General Purpose, Portrait	Action, Sports, BIF	Tilt-Shift, HDR†, Panorama	
	Lenses	11-400mm Zoom	11-400mm Zoom	100-400 Zoom	Tilt-Shift, Zoom, Macro	
	Exposure Mode	Manual-Auto ISO	Manual-Auto ISO	Manual	Manual 100	
	Metering Mode	Evaluative	Evaluative	Evaluative	Spot Partial Histogram	
	Drive Mode	Single	Single	High 7fps	Pano>Single HDR>High7	
	AF Mode	1-Shot or Servo	1-Shot or Servo	Servo	1-Shot, Servo (HDR)	
	AF Case	Case 1 Versatile	Case 6 Erratic	Case 6 Erratic	Case 1 Versatile	
	Flash	ISO set to 400	ISO set to 400	Yes	Yes	
D i a l	Main Dial	Aperture	Aperture	Aperture	Shutter Speed (HDR†)	
	Back Control Dial	Shutter Speed	Shutter Speed	Shutter Speed	Aperture (HDR†)	
	Back AF Switch	Exposure compensation	Exposure compensation	Exposure compensation	Exposure compensation	
B u t t o n	AF-ON button	1-Shot <> Servo	1-Shot <> Servo	1-Shot <> Servo	1-Shot <> Servo	
	Exposure Lock (* button)	FEL	FEL	FEL	FEL	
	AF Point Select (□ w/back switch)	Spot 1-Point 9-Point Zone □ Area	Spot 1-Point 9-Point Zone □ Area	Spot 1-Point 9-Point Zone □ Area	Spot 1-Point 9-Point Zone □ Area	
	T o p	M-fn →	WB/M→Dr/AF→FEC/ISO	WB/M→Dr/AF→FEC/ISO	WB/M→Dr/AF→FEC/ISO	WB/M→Dr/AF→FEC/ISO
		White Balance & Meter Mode	White Balance Metering Mode	White Balance Metering Mode	White Balance Metering Mode	White Balance Metering Mode
		Drive & AF	1-Shot <> Servo AF Point/Zone Select	1-Shot <> Servo AF Point/Zone Select	1-Shot <> Servo AF Point/Zone Select	1-Shot <> Servo AF Point/Zone Select
		Flash Exp Comp & ISO	Flash Exposure Comp. ISO setting	Flash Exposure Comp. ISO setting	Flash Exposure Comp. ISO setting	Flash Exposure Comp. ISO setting
	DOF (⊗)	Depth of Field	Depth of Field	Depth of Field	Depth of Field	
Lens (☉)	1-Shot <> Servo	1-Shot <> Servo	1-Shot <> Servo	1-Shot <> Servo		

Tilt-Shift Lenses: Manual focus, Focus Peaking & Focus Guides. | Panoramas: Manual focus & exposure, level tripod
 † HDR: Swap Av & Tv dials, Tv bracket = 5 shots, 1 or 1.3 EV steps, ISO = 100, H drive mode for 14-bit A/D, manual metering, manual or live view/touch focus, shutter release = touch or timer or RS-80N3 switch.

*** Custom Mode Settings: C1: 11-400mm Zoom, Manual-Auto ISO, Evaluative, Single, 1-Shot or Servo, Case 1 Versatile, ISO set to 400. C2: 100-400 Zoom, Manual, Evaluative, High 7fps, Case 6 Erratic, Yes. C3: 11-400mm Zoom, Manual 100, Spot Partial Histogram, Pano>Single HDR>High7, Case 1 Versatile, Yes.

Macro, Studio, Lens Tests: AV or MA mode, Live view & manual or touch focus, tripod, S1-E2 w/ multiple flashes, RS-80N3 or timer.