

R5 Mk II Custom Modes					
	Multi-Function M-Fn = C	C0	C1	C2	C3
	Use cases	General purpose	Action w/Pre-continuous, BIF	Constant light, aviation, BIF	Constant light, aviation, BIF
S E T U P	Exposure Mode	Manual w/ISO Auto	Manual w/ISO Auto	Manual	Manual
	Shutter/Image type	Electronic/CRAW	Electronic/CRAW	Electronic/CRAW	Electronic/CRAW
	AF servo character	Auto	Manual (Track -2, Acel +2)	Manual (Track -2, Acel +2)	Manual (Track -2, Acel +2)
	Whole area tracking AF	ON	ON	ON	ON
	Eye detection	Auto	Auto	Auto	Auto
	Pre-continuous	Disable	Enable ⇌ Disable (BIF)	Enable ⇌ Disable (BIF)	Disable
D I A L	Main dial = Aperture	Av	Av	Av	Av
	Quick Control dial = Speed	Tv	Tv	Tv	Tv
	Mode dial = Exp Comp./ISO	Exposure compensation	Exposure compensation	ISO	ISO
	Lens ring = Flash EC	Flash exposure comp.	Flash exposure comp.	Flash exposure comp.	Flash exposure comp.
B U T T O N	AF-ON = Direct AF area sel.	Spot, Whole area	Flexible Zone 1, Whole area	Flexible Zone 1, Whole area	Flexible Zone 1, Whole area
	* AE Lock button = Servo	One-shot ⇌ Servo	Servo ⇌ One-shot	Servo ⇌ One-shot	Servo ⇌ One-shot
	<input checked="" type="checkbox"/> AF point sel. = Drive	Single, High+ (15 fps)	Single, High+ (30 fps)	Single, High+ (30 fps)	Single, High+ (30 fps)
	DOF button = Eye Control	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF
	LCD panel button	Short=illum/long=Mode	Short=illum/long=Mode	Short=illum/long=Mode	Short=illum/long=Mode
Q U I C K C O N T R O L	PRE Pre-continuous	OFF	Action: Enable C1, BIF: OFF	Action: Enable C1, BIF: OFF	OFF
	AF Autofocus area	Spot ⇌ Whole frame	Spot ⇌ Whole frame	Flexible Zone 1 ⇌ Whole frame	Flexible Zone 1 ⇌ Whole frame
	Subject to detect	Auto/QC ()	Animals	Animals ⇌ vehicles	Animals ⇌ vehicles
	Eye control	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF
	Drive Mode	Single ⇌ High+ (15 fps)	High+ (30 fps)	High+ (30 fps)	Single ⇌ High+ (30 fps)
	External flash firing	Select flash control menu	Select flash control menu	Select flash control menu	Select flash control menu
	close Quick Control	Return to Display	Return to Display	Return to Display	Return to Display
	WB White balance	Auto	Auto	Auto	Auto
	Metering Mode	Evaluative	Evaluative	Evaluative	Evaluative
	One Shot ⇌ Servo AF op.	One-shot ⇌ Servo	Servo ⇌ One-shot	One-shot ⇌ Servo	One-shot ⇌ Servo
	Silent shutter function	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF	ON ⇌ OFF
	Screen/VF brightness	Manual/Auto	Manual/Auto	Manual/Auto	Manual/Auto
R5 Mk II My Menus					
Setup	Autofocus	Display	Configure	Customize/Network	
Pre-continuous	Shutter mode	Screen brightness	File name	Custom shooting mode C1-C3	
Subject to detect	Limit AF areas	Viewfinder brightness	Format card	Customize Quick Control	
ISO speed setting	Servo AF	Shooting info display	Record func+card/folder sel.	Airplane mode	
Battery info	Case Auto character	Blackout free display	Date/Time Zone	Network settings	
Restrict shooting modes C1 or C2	Tracking sensitivity	Display frame rate set	Image type/size	Bluetooth settings	
External Speedlite control	Accel/decel tracking	Power saving	Continuous shooting speed	Connect to smartphone	